

# MATOSHREE AGRO INDUSTRIES

At. Rahuari, Pst – Bhagur, Taluka – Dist . Nashik ( M.S) India.  
Ph no: 07020975890 / 09022041528  
Mail : sumit@coatingsandcoatings.co.in

## Fuel grade ethanol In LAB Test Report for Absolute (Anhydrous) Alcohol

		Test analysis
1.	Ethanol content, percent by volume at 15.6°C:	99.5%
2.	Miscibility with water:	Miscible
3.	Alkalinity:	Nil
4.	Acidity, as acetic acid, percent by weight, maximum:	0.004
5.	Residue on evaporation, percent by weight, maximum:	0.005
6.	Esters, as ethyl acetate, g/100 ml, maximum:	0.02
7.	Copper, as Cu, g/100 ml, maximum:	0.0002
8.	Lead, as Pb, g/100 ml, maximum:	0.00005
9.	Methyl alcohol:	To satisfy test.
10.	Fusel oil:	To satisfy test.
11.	Ketones, isopropyl alcohol and tertiary butyl alcohol:	To satisfy test.
12.	Total sulphur and sulphur compounds, as S, percent by weight, maximum:	0.0005
13.	Sulphur dioxide, as SO <sub>2</sub> , percent by weight, maximum:	0.0003
14.	Water content	0.09

Distillery Incharge.