



Shop Online : www.woodpol.net

PRODUCT INFORMATION SHEET

WOODPOL WOOD STAINS

PRODUCT CODE : 24

PRODUCT DESCRIPTION

WOODPOL WOOD STAINS are high quality solvent base stains which are used to give wood another color without masking the structure of the wood substrate, hence enhancing wood grains & texture. It penetrates in to the wood leaving a Natural look & so natural choice where aesthetic consideration is foremost. Generally they are applied directly on to the wood substrate, prior to filling or lacquering process.

Available in seven rich wood tone colors & also basic color like Red, Black, Blue, Orange, Yellow Green. These stains can inter-mix to make your own unique stains.



APPLICATION GUIDE

- | | | | |
|----|------------------------|---|--|
| 1 | Recommended use | : | Interior wood application. |
| 2 | Product Description | : | Solvent base wood stains. |
| 3 | Appearance | : | Transparent colors. |
| 4 | Consistency | : | Ready to use but can mix with good quality NC Thinner |
| 5 | Method of application | : | By ragging, spraying or mixing with lacquer. |
| 6 | Recoating time | : | 10 - 20 minutes. |
| 7 | Over coating time | : | 30 - 45 minutes. |
| 8 | Covering (theoretical) | : | 60 - 70 sq. ft. / coat / Lt, depending on wood type & porosity. |
| 9 | Shelf life | : | One year in unopened conditioned. |
| 10 | Packing | : | 100 ml, 1 Ltr, 5 Ltrs, 20 Ltrs. |
| 11 | Shades available | : | 0) Natural Wood 1) Rose wood 2) Walnut 3) LT Teak
4) Dark Antique Pine 5) Red Mahogany 6) Light Indian Oak
7) Red 8) Yellow 9) Orange 10) Brown 11) Blue 12) Green |

PERFORMANCE

- 1 Provides fast drying.
- 2 Ease of application.
- 3 Controlled penetration with uniform color.
- 4 Leaves no lap mark or streaks.
- 5 Enhance natural beauty of wood

APPLICATION PROCEDURE

- 1 Wood surface must be dry and free of dust and loose particles. Sand the surface along grains with emery paper # 180 followed by smooth sanding with # 320 or 400.
- 2 All stains are designed primarily for use on new wood.
- 3 Dip a clean sponge or folded cloth in to the stain and squeeze out the Excess. Using long continuous strokes, apply the stains to a small area at a time, following grain pattern of the wood. While application stop at a natural break to maintain a wet-edge to achieve uniform, lap-free, streak less finish.
- 4 The appearance and color of the stain will vary depending up on the wood porosity.
- 5 Apply additional coat at the interval of 10 – 15 minutes for desired wood tone color. To lighten the color, add good quality of NC thinner.
- 6 Do not sand the stain coat. Allow drying time of 30 – 45 minutes before over coating.
- 7 Apply finish coat or top coat of sealer, varnish, shellac, melamine or PU.

PRECAUTION

- 1 Since color of wood to be stained significantly affects the color of the finish, it is advisable to stain on small off-cut of wood of the same lot or hide portion of furniture to ensure the desired color is being achieved.
- 2 Not to be used on surface exposed to direct sun light.
- 3 Can be mix with melamine, NC lacquer. Never mix with polyurethane.
- 4 Recommended on new wood & not over previously stained surfaces.
- 5 Use rubber gloves to protect your hands from stains.
- 6 While mixing different stains, measure the proportions carefully to produce same color or tone if mixing is to be repeated.

GENERAL INFORMATION

- 1 Stir the content well before use.
- 2 Recoating time may be more in case of high humidity condition and / low ambient temperature.
- 3 Coverage varies depending on film thickness & nature of wood.

HEALTH AND SAFETY INFORMATION

- 1 Handle products in areas of good ventilation. Avoid inhaling vapors since product contains volatile organic solvents.
- 2 Wear normal protective overalls. Solvent resistant hand gloves, eye goggles are recommended. Avoid skin contact.
3. The product is flammable and container should therefore be kept away from fire & spark or any ignition source.

STORAGE, HANDLING & DISPOSAL

- 1 Store in original container in cool, dry & well ventilated place.
- 2 While handling, avoid inhalation & skin contact. Force ventilation or fresh air mask should be used in confined spaces.
- 3 Disposal in land filling & not in drain or water ways.

WARRANTY

The information contained in this sheet is based on our experience and laboratory tests and true to the best of our knowledge. However no warranty, expressed or implied, arising out of the use of our product is given as we have no control over the quality of substrate used nor the application conditions and methods. Customers are advised to carry out their own test to judge the suitability of our products for the recommended applications. The information contained here in is subject to change without further notice.

An ISO 9001:2008 Co.



Shop Online : www.woodpol.net

Coatings & Coatings (India) Pvt. Ltd.

MANUFACTURERS & EXPORTERS OF WOOD COATINGS, AUTO REFINISHES & ETHYL ALCOHOL

Corporate Office

104, Hill View Industrial Estate, 1st Floor, L.B.S. Marg, Behind R-City Mall, Amrut Nagar, Ghatkopar (W), Mumbai - 400 086. India. Tel.: +91-22-61847777, Fax.: +91-22-61847778 E-mail: salespolish@coatingsandcoatings.co.in Website: www.coatingsandcoatings.co.in